

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

1. Chemicals and enterprise identification

Product name and code: **Astra Sea Speed Tin-Free SPC**

Quality: Advanced Plus

Application of the substance: Antifouling

Product use: Coating-Solvent type

Colors: Oxide Red, Brown Red, Black
(other colors upon request)

Application Method: For professional use only

Supplier/manufacturer: Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588, E-mail: info@philacoatings.com

Website: www.philacoatings.com

Chemical emergency response numbers: 1-800-255-3924 for Domestic and +1-813-248-0585 for International.

Shipments of hazardous materials within the listed countries should reference ChemTel's in-county phone numbers:

Australia: 1-300-954-583, Brazil: 0-800-591-6042, China: 400-120-0751, India: 000-800-100-4086, Mexico: 01-800-099-0731

2. Hazards identification

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 (REACH), Annex II and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Pictograms:



Signal word: Danger

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

Hazard classification (GHS) and indication:

Flammable liquids	Category 2	H225	Highly flammable liquid and vapour
Flammable liquids	Category 3	H226	Flammable liquid and vapour
Acute toxicity Oral/Dermal	Category 4	H302	Harmful if swallowed
Acute toxicity Oral/Dermal	Category 4	H312	Harmful in contact with skin
Acute toxicity/Inhalation (Dust and Mists)	Category 4	H332	Harmful if inhaled
Skin corrosion/irritation	Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation	Category 2	H319	Causes serious eye irritation
Skin sensitizers	Category 1	H317	May cause an allergic skin reaction
Serious eye damage/eye irritation	Category 1	H318	Causes serious eye damage
Specific target organ toxicity, single exposure	Category 3	H336	May cause drowsiness or dizziness
Aquatic environmental hazards/Acute	Category 1	H400	Very toxic to aquatic life
Aquatic environmental hazard/Long-term	Category 1	H410	Very toxic to aquatic life with long lasting effects

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

3. Ingredient/composition information

Ingredient	Notes	Cas number	EC number	% by weight	Classification
Zinc oxide (ZnO)	-	1314-13-2	215-222-5	2.5-20	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Xylene	C	1330-20-7	215-535-7	10-25	Flam. Liq. 3, H226, Acute Tox. 4, H312, Acute Tox. 4, H332, Skin. Irrit. 2, H315 Eye Irrit. 2, H319
Cuprous oxide		1317-39-1	215-270-7	25-50	Acute Tox. 4, H302, Acute Tox. 4, H332, Eye Dam. 1, H318, Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Chloroparaffin	-	63449-39-8	264-150-0	2-3	Not classified
Rosin	-	8050-09-7	232-475-7	5-20	Skin Sens. 1, H317
Methyl isobutyl ketone	-	108-10-1	203-550-1	3-10	Flam. Liq. 2, H225, Eye Irrit. 2, H319, Acute Tox. 4, H332, STOT SE 3, H335
1-methoxy-2-propanol	-	107-98-2	203-539-1	0.5-2	Flam. Liq. 3, H226 STOT SE 3, H336
Nota Bene: Depending on local raw material and toxicant availability manufacturer reserves right without prejudice to use suitable variants* on same. *Other ingredients that do not contribute to the classification of the product.					

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

4. First-aid measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Ingestion: If swallowed, seek medical advice immediately and show the container or label.
Keep person warm and at rest. Do not induce vomiting.

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

5. Fire-fighting measures

Extinguishing media: Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Extinguishing media not to be used: Do not use water jet.

Recommendations: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

Cool closed containers exposed to fire with water.

Do not release runoff from fire to drains or watercourses.

6. Accidental release measures

Personal precautions: Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Spill: Preferably clean with a detergent. Avoid using solvents.

Note: See section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

Handling: Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

To dissipate static electricity during transfer, earth drums and connects to receiving container with bonding strap.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

Electrical equipment should be protected to the appropriate standard.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

When operators, whether spraying or not, must work inside the spray booth, ventilation is unlikely to be enough to control particulates and solvent vapor in all cases.

In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

Keep container tightly closed. Keep away from heat, sparks and flame.

No sparking tools should be used.

Storage: Store in accordance with local regulations. Observe label precautions.

Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

No smoking. Prevent unauthorized access.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.

Keep away from sources of ignition. Keep away from oxidizing agents, strong alkalis, strong Acids.

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

8. Exposure controls/personal protection

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved using local exhaust ventilation and good general extraction.

If these are not enough to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Ingredient name & Occupational exposure limits

Xylene:

EU OEL (Europe, 12/2017). Absorbed through skin.

STEL: 442 mg/m³ 15 minute(s).

STEL: 100 ppm 15 minute(s).

TWA: 221 mg/m³ 8 hour(s).

TWA: 50 ppm 8 hour(s).

Rosin:

EH40/2005 WELs (12/2011). Inhalation sensitizer.

STEL: 0.15 mg/m³ 15 minute(s). Form: Fume

TWA: 0.05 mg/m³ 8 hour(s). Form: Fume

1-methoxy-2-propanol:

EH40/2005 WELs (12/2011). Absorbed through skin.

STEL: 560 mg/m³ 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 375 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

Methyl isobutyl ketone:

EU OEL (Europe, 12/2017).

STEL: 208 mg/m³ 15 minute(s).

STEL: 50 ppm 15 minute(s).

TWA: 83 mg/m³ 8 hour(s).

TWA: 20 ppm 8 hour(s).

Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
xylene	DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

Predicted effect concentrations

Product/ingredient name	Compartment detail	Value	Method detail
Xylene	Fresh water	0.327 mg/l	-
	Marine water	0.327 mg/l	-
	Fresh water sediment	12.46 mg/kg	-
	Marine water sediment	12.46 mg/kg	-
	Soil	2.31 mg/kg	-
	Sewage Treatment Plant	6.68 mg/l	-

Personal protective equipment

Skin and body: Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.

Hands: Wear suitable gloves. Recommended, gloves (breakthrough time) > 8 hours: flour rubber, polyvinyl alcohol (PVA), nitrile rubber, 4H, Teflon. Not recommended, gloves (breakthrough time) < 1 hour: neoprene, butyl rubber, PVC.

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and considers the conditions of use, as included in the user's risk assessment.

Eyes: Use safety eyewear designed to protect against splash of liquids.

Respiratory system: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use respiratory mask with charcoal and dust filter when spraying this product (as filter combination A2-P3).

In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoal filter.

9. Physical and chemical properties

Physical state: Liquid.

Odor: Characteristic.

Color: Various colors.

Flash point: Closed cup: 28°C (82,4°F)

Density: 1.8 g/cm³

Explosion limits: 1.1 - 13.7%

Solubility: Insoluble in the following materials: cold water and hot water.

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis and strong acids.

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

11. Ecological information

Aquatic eco toxicity

Product/ingredient name	Test	Result	Species	Exposure
Cuprous oxide	Mortality	Acute EC50 0.042 mg/L Fresh water	Daphnia -Water flea - Daphnia similes - 6 to 24 hours	48 hours
	Mortality	Acute LC50 0.075 mg/L Fresh water	Fish - Zebra danio - Danio rerio	96 hours
Zinc oxide (ZnO)	Intoxication	Acute EC50 >1000 ppm Fresh water	Daphnia -Water flea - Daphnia magna - <24 hours	48 hours
	Mortality	Acute LC50 1.1 to 2.5 ppm Fresh water	Fish - Rainbow trout, Donaldson trout - Oncorhynchus, Mykiss	96 hours
Rosin	-	Acute EC50 >1000 mg/l	Algae	72 hours
	-	Acute EC50 911 mg/l	Daphnia	48 hours
	-	Acute LC50 >1000 mg/l	Fish	96 hours
Xylene	Mortality	Acute LC50 12000 to 16114 ug/L Fresh water	Fish - Bluegill - Leprosies macrochirus – 1.1 g	96 hours
Methyl isobutyl ketone	Intoxication	Acute EC50 3682 mg/L Fresh water	Daphnia -Water flea - Daphnia similes - 6 to 24 hours	24 hours

Ecological information

Biodegradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Cuprous oxide	-	-	Not readily
Xylene	-	-	Readily
Rosin	-	-	Not readily
Zinc oxide (ZnO)	-	-	Not readily

Bio accumulative potential

Product/ingredient name	LogKow	BCF	Potential
Xylene	3.12	8.1 to 25.9	Low
Rosin	1.9 – 7.7	56.3	Low
Zinc oxide (ZnO)	2.2	60960	High
Methyl isobutyl ketone	1.9	-	Low
1-methoxy-2-propanol	<1	-	Low

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

12. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements) and classified for toxicological hazards accordingly. See sections 2 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin.

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness in extreme cases and loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Swallowing may cause nausea, diarrhea, vomiting, gastro-intestinal irritation and chemical pneumonia.

Contains: rosin. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Exposure
Cuprous oxide	LC50 (Inhalation Vapor) 3.34 mg/l	Rat	4 hours
	LD50 (Dermal) 2000 mg/kg	Rat	-
	LD50 (Oral) 300 - 500 mg/kg	Rat	-
Xylene	LC50 (Inhalation Gas.) 5000 ppm	Rat	4 hours
	LC50 (Inhalation Vapor) 6350 ppm	Rat	-
	LD50 (Dermal) 4200 mg/kg	Rabbit	-
	LD50 (Oral) 3523 mg/kg	Rat	-
Chloroparafin	LD50 (Oral) >21.5 mg/kg	Rat	4 hours
	LD50 (Dermal) >10 mg/kg	Rabbit	-
Rosin	LD50 (Oral) 2800 mg/kg	Rat	4 hours
	LD50 (Dermal) 2000 mg/kg	Rat	-
Zinc oxide (ZnO)	LD50 (Oral) 5000 mg/kg	Rat	4 hours
	LD50 (Dermal) 2000 mg/kg	Rat	-
	LC50 (Inhalation Vapor) 5.7 mg/l	Rat	-
Methyl isobutyl ketone	LD50 (Dermal) 3000 mg/kg	Rabbit	4 hours
1-methoxy-2-propanol	LD50 (Oral) 6600 mg/kg	Rat	4 hours
	LD50 (Dermal) 1300 mg/kg	Rabbit	-

13. Disposal considerations

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorized waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

CONTAMINATED PACKAGING





Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in accordance with ADR/RID, IMDG/IMO and ICAO/IATA and national regulation.

International transport regulations

	UN Number	Proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards	Additional information
ADR/RID Class	UN 1263	PAINT	3 	III	Yes	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Tunnel restriction code (D/E)
IMDG/IMO Class	UN 1263	PAINT	3  	III	Yes	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules (EmS) F-E, S-E
ICAO/IATA Class	UN 1263	PAINT	3 	III	Yes	The environmentally hazardous substance mark may appear if required by other transportation regulations.

15. Regulatory information

EU regulations: The product is classified and labeled for supply in accordance with EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Not applicable.

Other EU regulations

Europe inventory: At least one component is not listed

Black List Chemicals: Not listed

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

Priority List Chemicals: Not determined

Industrial emissions (integrated pollution prevention and control) – Air: Listed

Industrial emissions (integrated pollution prevention and control) – Water: Not listed

Additional information: IMO Antifouling System Convention compliant (AFS/CONF/26)

This product does not contain organ tin compounds acting as biocides and complies with the International Convention on the Control of Harmful Anti-fouling Systems on Ships as adopted by IMO in October 2001 (IMO document AFS/CONF/26).

Industrial use: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

16. Other information

Abbreviations and acronyms:

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

EUH statement = CLP-specific Hazard statement

DNEL = Derived No Effect Level

RRN = REACH Registration Number

CEPE Classification: 1

Full text of abbreviated H statements referred to in sections 2 and 3:

H225 Highly flammable liquid and vapor

H226 Flammable liquid and vapor

H302 Harmful if swallowed

H312 Harmful in contact with skin

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H318 Causes serious eye damage

H319 Causes serious eye irritation

H332 Harmful if inhaled

H336 May cause drowsiness or dizziness

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

H411 Toxic to aquatic life with long-lasting effects

Full text of classifications [CLP/GHS]:

Acute Tox. 4, H302 ACUTE TOXICITY (oral) - Category 4

Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4

Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4

Aquatic Acute 1, H400 ACUTE AQUATIC HAZARD - Category 1

Philadelphia Coatings LLC

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



Safety Data Sheet

Aquatic Chronic 1, H410 LONG-TERM AQUATIC HAZARD - Category 1

Aquatic Chronic 2, H411 LONG-TERM AQUATIC HAZARD - Category 2

Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2

Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3

Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1

STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

This Safety Data Sheet is prepared in accordance with according to Regulation (EC) No. 1272/2008 [CLP/GHS].

Notice To Whom It May Concern:

Your attention and information in this MSDS are based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.