

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



## Safety Data Sheet

### 1. Chemicals and enterprise identification

Product name and code: **PHILADUR Shop Primer PHE 70 Comp. A**

Application of the substance: **Two component shop primer epoxy**

Product use: **Coating Solvent-borne**

Colors: **Oxide Red**

Supplier/manufacturer: **Philadelphia Coatings LLC**

Americas Office: 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588, E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)

Chemical emergency response numbers: 1-800-255-3924 for Domestic and +1-813-248-0585 for International.

Shipments of hazardous materials within the listed countries should reference ChemTel's in-county phone numbers:

Australia: 1-300-954-583, Brazil: 0-800-591-6042, China: 400-120-0751, India: 000-800-100-4086, Mexico: 01-800-099-0731

### 2. Hazards identification

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 (REACH), Annex II and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Pictograms:



Signal word: Danger

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



## Safety Data Sheet

### Hazard classification (GHS) and indication:

Flammable liquids	Category 1	H224	Extremely flammable liquid and vapour
Flammable liquids	Category 2	H225	High flammable liquid and vapour
Flammable liquids	Category 3	H226	Flammable liquid and vapour
Acute toxicity Oral	Category 1	H301	Toxic if swallowed
Acute toxicity Oral	Category 4	H302	Harmful if swallowed
Aspiration Hazard	Category 1	H304	May be fatal if swallowed and enters airways
Acute Toxicity Dermal	Category 3	H311	Toxic in contact with skin
Acute toxicity Dermal	Category 4	H312	Harmful in contact with skin
Acute toxicity/Inhalation	Category 3	H331	Toxic if inhaled
Acute toxicity/Inhalation (Dust and Mists)	Category 4	H332	Harmful if inhaled
Skin corrosion/irritation	Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation	Category 2	H319	Causes serious eye irritation
Specific target organ toxicity, single exposure	Category 3 (respiratory tract irritation)	H335, H336	May cause respiratory irritation. May cause drowsiness or dizziness
Reproductive Toxicity	Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity, single exposure	Category 1	H370	Causes damage to organs
Specific target organ toxicity, single exposure	Category 2	H371	May cause damage to organs
Specific target organ toxicity, repeated exposure	Category 1	H372	Causes damage to organs through prolonged or repeated exposure
Specific Target Organ toxicity - repeated exposure	Category 2	H373	May cause damage to organs through prolonged or repeated exposure

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



## Safety Data Sheet

Aquatic environmental hazards/Acute	Category 3	H402	Harmful to aquatic life
Aquatic environmental hazards/Chronic	Category 3	H412	Harmful to aquatic life with long lasting effects

### 3. Ingredient/composition information

Chemical name	Notes	Cas number	EC number	% by weight	Classification
xylene	C	1330-20-7	215-535-7	9 - 26	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315
Toluene	-	108-88-3	203-625-9	25 - 50	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2 H315 STOT SE 3, H336 Rep. Tox. 2, H361 STOT RE 2, H373 Acute Tox. 4, H302
ethanol	-	64-17-5	200-578-6	1 - 3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT RE 1, H370 Flam. Liq. 3 H226, Acute Tox. 3, H301 H311 Acute Tox. 3, H331 STOT RE 2, H371 Acute Tox. 4, H302 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
butanone; Methyl-Ethyl-Ketone	-	78-93-3	201-159-0	10 - 25	Flam. Liq. 2, H225 Skin Irrit. 2 H315, Eye Irrit. 2, H319, Acute Tox. 4 H332 STOT SE 3, H335 STOT SE 3, H336 STOT SE 2, H371 STOT RE 1, H372
amines, n-tallow alkyltrimethylenedi-, oleates	-	61791-53-5	263-186-4	0.3 - 1	Flam. Liq. 1, H224 Flam. Liq. 2, H225

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

### 4. First-aid measures

**General:** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

**Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

**Skin contact:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



---

## Safety Data Sheet

---

**Inhalation:** Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**Ingestion:** If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

### 5. Fire-fighting measures

**Extinguishing media:** Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Extinguishing media not to be used:** Do not use water jet.

**Recommendations:** Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

### 6. Accidental release measures

**Personal precautions:** Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

**Spill:** Preferably clean with a detergent. Avoid using solvents.

**Note: see section 8 for personal protective equipment and section 13 for waste disposal.**

### 7. Handling and storage

**Handling:** Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

When operators, whether spraying or not, must work inside the spray booth, ventilation is unlikely to be enough to control particulates and solvent vapor in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

**Storage:** Store in accordance with local regulations. Observe label precautions. Store in a dry, cool and well-ventilated area.

Keep away from heat and direct sunlight. No smoking. Prevent unauthorized access.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



## Safety Data Sheet

Do not empty into drains. Keep away from sources of ignition.

Keep away from oxidizing agents, strong alkalis, strong acids.

### 8. Exposure controls/personal protection

**Engineering measures:** Provide adequate ventilation. Where reasonably practicable, this should be achieved using local exhaust ventilation and good general extraction. If these are not enough to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

#### Ingredient name & Occupational exposure limits

**Xylene: EH40/2005-WELs (8/2007). Absorbed through skin.**

STEL: 651 mg/m<sup>3</sup> 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 434 mg/m<sup>3</sup> 8 hour(s).

TWA: 100 ppm 8 hour(s).

**Toluene: EH40/2005-WELs (12/2011). Absorbed through skin.**

STEL: 560 mg/m<sup>3</sup> 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 375 mg/m<sup>3</sup> 8 hour(s).

TWA: 100 ppm 8 hour(s).

**butanone; ethyl methyl ketone: EH40/2005-WELs (12/2011).**

STEL: 885 mg/m<sup>3</sup> 15 minute(s).

STEL: 300 ppm 15 minute(s).

TWA: 590 mg/m<sup>3</sup> 8 hour(s).

TWA: 200 ppm 8 hour(s).

**Ethanol: EH40/2005-WELs (8/2007). Absorbed through skin.**

STEL: 1000 ppm 15 minute(s).

TWA: 1900 mg/m<sup>3</sup> 8 hour(s).

TWA: 1000 ppm 8 hour(s).

#### Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
xylene	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
toluene	DNEL	Long term Inhalation	192 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	384 mg/kg	Workers	Systemic

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



## Safety Data Sheet

### Predicted effect concentrations

Product/ingredient name	Compartment detail	Value
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Fresh water sediment	12.46 mg/kg
	Marine water sediment	12.46 mg/kg
	Soil	2.31 mg/kg
	Sewage Treatment Plant	6.68 mg/l
toluene	Fresh water	0.68 mg/l
	Marine water	0.68 mg/l
	Fresh water sediment	16.39 mg/kg
	Marine water sediment	16.39 mg/kg
	Soil	2.89 mg/kg
	STP	13.61 mg/l

### Personal protective equipment

**Skin and body:** Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Hands:** Wear suitable gloves. Recommended, gloves (breakthrough time) > 8 hours: Viton, Responder, nitrile rubber, 4H, Teflon. May be used, gloves (breakthrough time) 4 - 8 hours: neoprene, butyl rubber. Not recommended, gloves (breakthrough time) < 1 hour: polyvinyl alcohol (PVA), PVC. For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and considers the conditions of use, as included in the user's risk assessment.

**Eyes:** Use safety eyewear designed to protect against splash of liquids.

**Respiratory system:** If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use respiratory mask with charcoal and dust filter when spraying this product. (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoal filter.

## 9. Physical and chemical properties

**Physical state:** Liquid.

**Odor:** Characteristic.

**Color:** Various colors.

**Flash point:** Closed cup: - 5°C (23°F)

**Density:** 1.14 g/cm<sup>3</sup>

**Viscosity:** Kinematic (40°C (104°F)) >0.225 cm<sup>2</sup> /s (>22.5 mm<sup>2</sup> /s)

**Solubility:** Insoluble in the following materials: cold water and hot water.

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



## Safety Data Sheet

### 10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7). Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

### 11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 15 for details. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Swallowing may cause nausea, diarrhea, vomiting, gastro-intestinal irritation and chemical pneumonia.

### Acute toxicity

Product/ingredient name	Result	Species	Exposure
Xylene	LC50 (Inhalation Vapor) 11 ppm	Rat	4 hours
	LD50 (Dermal) 1100 mg/kg	Rat	4 hours
	LD50 (Oral) 2100 mg/kg	Rat	4 hours
Toluene	LD50 (Oral) 5580 mg/kg	Rat	4 hours
	LD50 (Dermal) 12124 mg/kg	Rat	4 hours
	LC50 inhalation 28.6 mg/l	Rat	4 hours
Ethanol	LC50 (Inhalation) 124700 mg/m <sup>3</sup>	Rat	4 hours
	LD50 (Oral) 7 g/kg	Rat	4 hours

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: info@philacoatings.com

Website: www.philacoatings.com



## Safety Data Sheet

### 12. Ecological information

#### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
xylene	Mortality	Acute LC50 12000 to 16114 ug/l Fresh water	Fish - Bluegill -Lepomis macrochirus-1.1g	96 hours
butanone; ethyl methyl ketone	Population	Acute EC50 500000 mg/l Marine water	Algae	96 hours
	Mortality	Acute LC50 530 mg/l Fresh water	Fish	96 hours
Toluene	-	Chronic NOEC <500000 mg/l Fresh water	Algae- Pseudokirchneriella subcapitata (green algae)	96 hours
		Chronic NOEC 1000 mg/l Fresh water	Daphnia - Daphnia magna	21 hours
Ethanol	-	Acute EC50 2000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
		Acute LC50 42000 mg/l Fresh water	Fish - Oncorhynchus mykiss	4 days

### Ecological information

#### Biodegradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
Ethanol	-	-	Readily

#### Bioaccumulative potential

Product/ingredient name	LogKow	BCF	Potential
xylene	3.12	8.1 to 25.9	low
Toluene	2.73	13	low
butanone; ethyl methyl ketone	0,3	-	low
ethanol	-0,35	-	low

### 13. Disposal considerations

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.



# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



## Safety Data Sheet





**European waste catalogue (EWC):** 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

### 14. Transport information

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in accordance with ADR/RID, IMDG/IMO and ICAO/IATA and national regulation.

#### International transport regulations

	UN Number	Proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards	Additional information
ADR/RID Class	UN 1263	PAINT	3 	III	No	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Tunnel restriction code (D/E)
IMDG/IMO Class	UN 1263	PAINT	3  	III	Yes	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules (EmS) F-E, S-E
ICAO/IATA Class	UN 1263	PAINT	3 	III	No	The environmentally hazardous substance mark may appear if required by other transportation regulations.

### 15. Regulatory information

**EU regulations:** The product is classified and labeled for supply in accordance with EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles:

Not applicable.

Other EU regulations

Europe inventory: At least one component is not listed

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



---

## Safety Data Sheet

---

Black List Chemicals: Not listed

Priority List Chemicals: Not determined

Industrial emissions (integrated pollution prevention and control) – Air: Listed

Industrial emissions (integrated pollution prevention and control) – Water: Not listed

**Industrial use:** The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

### 16. Other information

Abbreviations and acronyms:

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

EUH statement = CLP-specific Hazard statement

RRN = REACH Registration Number

DNEL = Derived No Effect Level

**CEPE Classification:** 1

#### Full text of abbreviated H statements referred to in sections 2 and 3:

H224 Extremely flammable liquid and vapour

H225 High flammable liquid and vapour

H226 Flammable liquid and vapor

H301 Toxic if swallowed

H302 Harmful if swallowed

H304 May be fatal if swallowed and enters airways

H311 Toxic in contact with skin

H312 Harmful in contact with skin

H315 Causes skin irritation

H319 Causes serious eye irritation

H331 Toxic if inhaled

H332 Harmful if inhaled

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H361 Suspected of damaging fertility or the unborn child

H370 Causes damage to organs

H371 May cause damage to organs

H372 Causes damage to organs through prolonged or repeated exposure

H373 May cause damage to organs through prolonged or repeated exposure

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects

# Philadelphia Coatings LLC

Americas Office; 6 Georgian Row, The Woodlands, Texas, TX 77380, USA

Tel: +1 832-948-5588

E-mail: [info@philacoatings.com](mailto:info@philacoatings.com)

Website: [www.philacoatings.com](http://www.philacoatings.com)



---

## Safety Data Sheet

---

### Full text of classifications [CLP/GHS]:

Aquatic Acute 3, H402 LONG-TERM AQUATIC HAZARD - Category 3

Aquatic Chronic 3, H412 LONG-TERM AQUATIC HAZARD - Category 3

Flam. Liq. 1, H224 FLAMMABLE LIQUIDS - Category 1

Acute Tox. 3, H301 ACUTE TOXICITY (oral) - Category 3

Acute Tox. 4, H302 ACUTE TOXICITY (Oral) - Category 4

Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1

Acute Tox. 3, H311 ACUTE TOXICITY (Dermal) - Category 3

Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4

Acute Tox. 3, H331 ACUTE TOXICITY (inhalation) - Category 3

Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4

Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Flam. Liq. 3, H225, H226 FLAMMABLE LIQUIDS - Category 3

Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2

STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Rep. Tox. 2, H361 REPRODUCTIVE TOXICITY - Category 2

STOT SE 1, H370 SPECIFIC TARGET ORGAN TOXICITY, SINGLE EXPOSURE - Category 1

STOT SE 2, H371 SPECIFIC TARGET ORGAN TOXICITY, SINGLE EXPOSURE - Category 2

STOT RE 1, H372 SPECIFIC TARGET ORGAN TOXICITY, REPEATED EXPOSURE - Category 1

STOT RE 2, H373 (hearing organs) SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

**This Safety Data Sheet is prepared in accordance with according to Regulation (EC) No. 1272/2008 [CLP/GHS].**

### Notice to whom it may concern:

Your attention and information in this MSDS are based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this MSDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.